


PosiTector® Inspection Kits

Each Inspection Kit contains:

- PosiTector Gage Body—Standard or Advanced
- PosiTector **6000** Coating Thickness Probe—select from a variety of measurement ranges and probe styles
- PosiTector **DPM** Environmental Probe
- PosiTector **SPG** Surface Profile Probe



KITF3 Shown



WiFi



DeFelsko®

The Measure of Quality

PosiTector body accepts all PosiTector **6000**, **DPM** and **SPG** probes easily converting from a coating thickness gage to a dew point meter or surface profile gage.

Select **Standard** or **Advanced** Features for a complete comparison visit www.defelsko.com/kits/kit_features.htm

Each Standard Kit contains the **PosiTector Standard** gage body and 3 probes—coating thickness, environmental and surface profile.

Features include:

- Monochrome display with transfective technology enhances sunlight readability
- Gage stores readings for one probe at a time

Coating Thickness with Standard Models

- Storage of 250 readings—stored readings can be viewed or downloaded

Environmental Monitoring with Standard Models

- Storage of 2,500 datasets (RH, Ta, Ts, Td, Ts-Td). Stored readings can be viewed or downloaded.
- Auto Log Mode automatically records all 5 parameters at user selected time intervals. Runs unattended on batteries for up to 50 hours or continuously via USB

Surface Profile with Standard Models

- Storage of 250 readings—stored readings can be viewed or downloaded

Each Advanced Kit contains the **PosiTector Advanced** gage body and 3 probes—coating thickness, environmental and surface profile.

Features include:

- Hi Contrast reversible color LCD
- Storage of 100,000 readings in up to 1,000 batches and sub-batches

Easily store thickness, climatic conditions and profile height in multiple batches.

- Batch annotation—add notes, change batch names and more with built-in QWERTY keyboard
- Onscreen help, real time graphing, picture prompting and more
- WiFi technology wirelessly synchronizes with PosiSoft.net, downloads software updates, and connects to mobile devices for expanded functionality
- Data transfer via USB to a PC or via Bluetooth Wireless Technology to a PC or printer

Coating Thickness with Advanced Models

- Multiple stored calibration adjustments for measuring on a variety of substrate conditions
- SSPC PA2 feature determines if film thickness over a large area conforms to user-specified min/max levels
- FSPC 90/10 feature determines if a coating system complies with an IMO performance standard for protective coatings

Environmental Monitoring with Advanced Models

- Storage of 20,000 datasets (RH, Ta, Ts, Td, Ts-Td) in up to 1,000 batches. Stored readings can be viewed or downloaded.
- Auto Log Mode automatically records all 5 parameters at user selected time intervals. Data can be streamed via USB or Bluetooth at each interval. Runs unattended on batteries for up to 8 months or continuously via USB
- User defined limits for all parameters with visible and audible warnings
- Wet bulb temperature can be displayed
- Trend charts graph readings in real-time

Surface Profile with Advanced Models

- SmartBatch™ allows entry of user-defined parameters and criteria to comply with various standards and test methods

Custom Inspection Kits

- Build your own Inspection Kit from a selection of gage bodies and probes to suit your needs.
- Universal body accepts all PosiTector **6000**, **200**, **DPM**, **SPG** and **UTG** probes



Kits Come Complete with a gage body (Standard or Advanced), coating thickness probe (user selected), environmental probe, surface profile probe, precision plastic shims, glass zero plate and metal shim, protective rubber holster with belt clip, wrist strap, 3 AAA alkaline batteries, 3 instruction manuals, hard shell case, protective lens shield, 3 Long Form Certificates of Calibration traceable to NIST or PTB, USB cable and 2 year warranty on gage body and probes.

Case Size: 30 cm (L) x 25 cm (W) x 10 cm (D); 12" (L) x 10" (W) x 4" (D)

Weight: 1.3 kg (2.8 lbs.)



Ordering Guide

Inspection Kit	PosiTector Body	Coating Thickness Probe
KITF1	Standard	6000-F
KITFS1		6000-FS
KITFN1		6000-FN
KITFNS1		6000-FNS
KITF3	Advanced	6000-F
KITFS3		6000-FS
KITFN3		6000-FN
KITFNS3		6000-FNS