

# COVALENCE<sup>®</sup> PERP

## Product Information

Repair system for damaged mill-applied PE coating.

**Product description:** Covalence<sup>®</sup> PERP is a heat-applied patch which, in combination with mastic filler, offers an economically effective and high quality repair system for factory PE pipe coatings damaged mechanically during transportation, storage and laying of pipes. PERP, PERP80 and PERP60E are designed to repair the damaged areas on line coatings, mainly 2 or 3 layer PE. PERP60E is designed to repair the damaged areas on PE coated pipes used in high shear applications, such as directional drilling.

- **Sleeves:** are recommended for large damaged areas (see selection table below).
- **Filler tape:** is used to fill the holiday, thus restoring the mill-applied coating thickness of the pipe.
- **Epoxy primer:** is additionally used when reinstatement of the epoxy layer is required.

Construction: Two-layer or three-layer system:

- **First layer:** Liquid epoxy, solvent-free two-component (optional).
- **Second layer:** Copolymer adhesive
- **Third layer:** Radiation cross-linked, high density polyethylene (unexpanded).

Installation is done with standard gas torches. To repair a damaged area, installers round out, roughen, clean and preheat the area and apply the filler tape to fill out the holiday. PERP, cut to size, is positioned onto the treated area and heated. During heating, the adhesive softens and flows to form a tight bond with the substrate. The bond strength builds up during cool-down and is fully retained after job completion.

### Features:

- Adaptable repair system.
- Resistant to high shear forces.
- Excellent adhesion to commercial, PE mill-applied coatings.
- No special equipment required.

### Benefits:

- Long lasting and high performance.
- Provides a virtually monolithic coating repair of high quality.
- Saves time with fast and convenient installation. Saves money by keeping inventory and logistics costs low.
- Makes installation fast and easy. Keeps installation costs low.

## Product selection guide

	PERP	PERP80	PERP60E
<b>Max operating temperature</b>	65°C (149°F)*	80°C (176°F)	60°C (140°F)
<b>Compatible line coatings</b>	PE, FBE, PP, PU	PE, FBE, CTE	PE, FBE
<b>Min. preheat temperature</b>			
<b>Bare metal</b>	70-80°C (158-176°F)	70-80°C (158-176°F)	70-80°C (158-176°F)
<b>Line coating</b>	70-80°C (158-176°F)	90-100°C (194-212°F)	70-80°C (158-176°F)
<b>Recommended pipe preparation</b>	ST3 or SA2½	ST3 or SA2½	SA2½
<b>Filler tape</b>	S1137-50X3X3000	S1137-50X3X3000	S1182-50X3X3000
<b>Epoxy primer (optional)</b>	S1239 or S1301-M	S1301-M or S1401(-M)	S1239 or S1301-M
<b>Soil stress restrictions</b>	None	None	None
<b>Performance</b>	EN12068, Class C50	EN12068, Class C80	EN12068, Class C60

\* Max. 70°C (158°F) when used a repair to HSS under infill.

## Product properties

### Backing

Property	Test method	Typical value PERP, PERP80 & PERP60E
<b>Tensile strength at break</b>	ASTM D-638	3300 psi 22.8 MPa
<b>Elongation at break</b>	ASTM D-638	600%
<b>Hardness, Shore D</b>	ASTM D-2240	55
<b>Shrink force</b>	ASTM D-638 @ 150°C (302°F)	40 psi
<b>Dielectric strength</b>	ASTM D-149	900 V/mil 35 kV/mm
<b>Moisture absorption</b>	ASTM D-570	0.05%

### Adhesive

Property	Test method	Typical value		
		PERP	PERP80	PERP60E
<b>Softening point</b>	ASTM E-28	103°C (217°F)	120°C (248°F)	94°C (201°F)
<b>Shear strength</b>	ASTM D-1002	350 psi @ 23°C (73°F)	750 psi @ 23°C (73°F)	500 psi @ 23°C (73°F)
		11 psi @ 65°C (149°F)	65 psi @ 80°C (176°F)	87 psi @ 50°C (122°F)
	EN12068	0.22 N/mm <sup>2</sup> @ 50°C (122°F)	0.12 N/mm <sup>2</sup> @ 80°C (176°F)	0.32 N/mm <sup>2</sup> @ 60°C (140°F)

### Installed sleeve

Property	Test method	Typical value		
		PERP	PERP80	PERP60E
<b>Peel to PE</b>	ASTM D-1000	25 lb/in	21 lb/in	60 lb/in
	EN12068	3.5 N/mm	3.5 N/mm	20 N/mm
<b>Impact resistance</b>	EN12068, Class C	>15 J	>15 J	>15 J
<b>Indentation</b>	EN12068, Class C	Pass @ 50°C (122°F)	Pass @ 80°C (176°F)	Pass @ 60°C (140°F)

Note: The typical values in this data sheet are based on lab prepared samples. Values shown are not to be interpreted as product specifications.

## Product thickness

	PERP - PERP80	PERP60E
<b>Backing as supplied</b>	0.76 mm (0.030 in)	0.76 mm (0.030 in)
<b>Adhesive as supplied</b>	0.65 mm (0.026 in)	0.80 mm (0.031 in)

Order information		General order information	
Covalence® PERP type products are available – As a kit – As a roll		<b>Installation guide</b> For proper product installation, see latest installation instruction.	<b>Handling</b> Handle with care. Keep boxes upright.
<b>Example:</b>		<b>Storage</b> Store indoor, clean and dry, away from direct sunlight in a cool place below +50°C. Unlimited shelf life.	<b>Information</b>
<b>Standard ordering options</b>		<b>Documentation</b> Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending an email to <a href="mailto:info@sealforlife.com">info@sealforlife.com</a>	<b>Certified staff</b> Application of the described coating system shall be carried out by certified personnel.
<b>PERP-KIT</b>	1 pc PERP patch 170 mm x140 mm with rounded corners, 1 pc S1137 (50x3x25 mm), 1 pc abrasive paper P60 (150x50 mm), installation instruction <i>For damaged areas less than 40x70 mm</i>		
<b>PERP-170X10,000</b>	Roll of 10 m (32.5 ft) length, 170 mm (6.75") width		
<b>PERP-425X10,000</b>	Roll of 10 m (32.5 ft) length, 438 mm (17.25") width		
<b>PERP80-425X1000-PCI</b> <b>PERP60E-425X10,000PCI</b> <b>S1137-50x3x3000</b>	PCI = Permanent Change Indicator (embossed backing) 50 mm (2") wide, 3 mm (0.12") thick, 3 m (10 ft) long Filler adhesive for PERP + PERP80 <i>Filler adhesive, necessary where PERP rolls are used. NOTE: 3 rolls of filler per roll of PERP are recommended.</i>		
<b>S1182-50X1X9000</b>	50 mm (2") wide, 1 mm (0.039") thick, 9 m (30 ft) long Filler adhesive for PERP60E <i>Filler adhesive, necessary where PERP60E rolls are used. NOTE: 3 rolls of filler per roll of PERP are recommended.</i>		
<b>PERP-280X280-05</b>	Kit of 2 pcs PERP-280x140-05 with punched hole <i>To be used with HTTE, house tap tee protection</i>		
<b>S1239 or S1301-M</b> <b>S1301-M or S1401(-M)</b>	<b>Epoxy primer</b> For PERP + PERP60e For PERP80 <i>Only when 3-layer coating</i>		

Application table	
Max.damaged area for using PERP. *	
Pipe diameter	Max.damage
<10"	50 mm x 50 mm
<30"	100 mm x 100 mm
>= 30"	150 mm x 150 mm

\* For larger damaged areas, the use of heat-shrinkable sleeves is recommended (refer to Covalence girth weld sleeves).

Local Distributor / Representative:



**MSP**  
MATSERVICE PETRÓLEO

For contact details of local Distributors / Representatives



Seal For Life Industries LLC  
Franklin, MA, USA  
Tel: +1 508 918 1600  
Toll Free: +1 800 248 7659  
Fax: +1 508 918 1905  
franklin@sealforlife.com

Seal For Life Industries Mexico  
S de R.L. de C.V.  
Tijuana, Mexico  
Tel USA: +1 858 633 9797  
Fax USA: +1 858 633 9740  
Tel Mx: +52 664 647 4397  
Fax Mx: +52 664 607 9105  
mexico@sealforlife.com

Seal For Life Industries  
Stopaq B.V.  
Stadskanaal, the Netherlands  
Tel: +31 599 696 170  
Fax: +31 599 696 177  
info@sealforlife.com

Seal For Life Industries BVBA  
Westerlo, Belgium  
Tel: +32 14 722 500  
Fax: +32 14 722 570  
belgium@sealforlife.com

Seal For Life India Private Ltd.  
Baroda, India  
Tel: +91 2667 264 721  
Fax: +91 2667 264 724  
india@sealforlife.com

Anodefex® - Stopaq® - Polyken® - Covalence® - Powercrete® - Sealtaq® - Blockr® - Easy.Qote®

DISCLAIMER: Seal For Life Industries warrants that the product(s) represented within conform(s) to its/their chemical and physical description and is appropriate for the use as stated on the respective technical data sheet when used in compliance with Seal For Life Industries written instructions. Since many installation factors are beyond the control of Seal For Life Industries, the user is obligated to determine the suitability of the products for the intended use and assume all risks and liabilities in connection herewith. Seal For Life Industries liability is stated in the standard terms and conditions of sale. Seal For Life Industries makes no other warranty either expressed or implied. All information contained in the respective technical data sheet(s) should be used as a guide and is subject to change without notice. This document supersedes all previous revisions. Please see revision date on the left. Covalence® is a registered trademark of Seal For Life Industries.